

# Passive Air Sampling Kits



Superior Performance—  
an Excellent Restek Value.

- Improved design eliminates leaks at the filter.
- Siltek<sup>®</sup> treated components ensure an exceptionally inert surface.
- Excellent for sampling times from 0.5 hour to 125 hours, or grab sampling.

**HROMalytic Chromatography**  
**Australian Distributors** **ECHnology** **Products '08**  
[www.chromtech.net.au](http://www.chromtech.net.au) E-mail : [info@chromtech.net.au](mailto:info@chromtech.net.au) Tel : +61 3 9762 2034 Fax : +61 3 9761 1169

**RESTEK**

**RESTEK**

**Chromatography Products**

[www.restek.com](http://www.restek.com) 800-356-1688 • 814-353-1300

## Passive Air Sampling Kits

Restek's passive air sampling kit incorporates all the hardware necessary to collect air samples, and is easy to assemble for field sampling.\* The improved filter design greatly reduces the number of potential leak sites.

The passive air sampling kit is available in seven sampling flow ranges, and in stainless steel or Siltek® treated finish. The stainless steel kit is ideal to partner with the Restek TO-Can™ air sampling canister for TO-14A and TO-15 methods. Use the Siltek® treated version with the Restek SilcoCan™ air sampling canister when collecting low-level volatile sulfur compounds, or other active compounds.

### 1. Veriflo™ SC423XL flow controller


This flow controller is the heart of the sampling train. It is a high-quality device designed to maintain a constant mass flow as the pressure changes from 30" Hg to 5" Hg (we recommend you stop sampling at or before 5" Hg of vacuum). All wetted parts of the flow controller can be Siltek® treated.

### 2. Stainless steel vacuum gauge

Fitted to the flow controller, the gauge monitors canister vacuum changes during sampling.

### 3. 1/4-inch Siltek® sample inlet

The 0.3m x 1/4-inch tubing includes a stainless steel nut on the inlet end, to prevent water droplets from accumulating at the edge of the tubing, where they could be pulled into the sampling train.



All fitting connections are 1/4" tube, except where noted.



### 4. 2-micron frit filter and washer

Located prior to the critical orifice to prevent airborne particles from clogging the critical orifice. Easily replaceable and available in stainless steel, or Siltek® treated for optimum inertness.

### 5. Interchangeable critical orifice

An interchangeable ruby critical orifice allows you to control the flow with very high precision. To select the correct critical orifice for your sample, see table below. Available in stainless steel, or Siltek® treated for optimum inertness.

## Air Sampling Kits

400cc	Canister Volume*/Sampling Time				Flow (sccm)	Orifice size	Siltek® Treated Sampling Kits	Stainless Steel Sampling Kits
	1 Liter	3 Liter	6 Liter	15 Liter				
8 hour	24 hour	48 hour	125 hour	—	0.5–2	0.0008"	24217	24216
2 hour	4 hour	12 hour	24 hour	60 hour	2–4	0.0012"	24160	24165
1 hour	2 hour	6 hour	12 hour	30 hour	4–8	0.0016"	24161	24166
—	1 hour	4 hour	8 hour	20 hour	8–20	0.0020"	24162	24167
—	—	2 hour	3 hour	8 hour	20–40	0.0030"	24163	24168
—	—	—	1.5 hour	4 hour	40–80	0.0060"	24164	24169
—	—	—	0.5 hour	1 hour	80–350	0.0090"	22101	22100

\*Air sampling canisters sold separately.

Restek Trademarks:  
Siltek, TO-Can, SilcoCan, Restek logo.

Other Trademarks:  
Veriflo (Veriflo Corp)



Lit. Cat.# 580137

© 2007 Restek Corporation.

**HROMalytic Chromatography Products '08**  
**Australian Distributors ECHnology**  
 www.chromtech.net.au E-mail : info@chromtech.net.au Tel : +61 3 9762 2034 Fax : +61 3 9761 1169

