









COLUMN INSTALLS THIS END

| Liners for Varian 1078/1079 Injection Ports | Benefits/Uses: | ID* OD x Length | Similar to Varian part # | ea. | cat.#/price 5-pk. | 25-pk. |
|---|-------------------------------------|------------------------|-----------------------------|-------|----------------------|--------|
|  1078/1079 Split w/CarboFrit | dirty samples, non-active compounds | 3.4mm 5.0mm x 54mm | 392611946 | 21708 | 21709 | — |
|  1078/1079 Splitless | trace samples <2µL | 2.0mm 5.0mm x 54mm | 392611947 | 21711 | 21712 | — |
|  Open 0.5mm ID | trace samples <1µL | 0.5mm 5.0mm x 54mm | 392611949 | 20992 | 20993 | — |
|  1078/1079 Split-No Frit | active samples | 3.4mm 5.0mm x 54mm | 392611945 | 20859 | 20901 | 20909 |
|  Open 0.75mm ID | trace, low volume samples | 0.75mm 5.0mm x 54mm | 392611948 | 21714 | 21715 | 21716 |
|  1078/1079 Split Precision Liner w/Wool | dirty samples, trace samples | 3.4mm 5.0mm x 54mm | — | 21024 | 21025 | — |

| DI Liners for Varian 1078/1079 Injection Ports (For 0.25/0.32/0.53mm ID Columns) | Benefits/Uses | ID* OD x Length | Similar to Varian part # | cat.#/price ea. | cat.#/price 5-pk. |
|--|--|-----------------------|-----------------------------|--------------------|----------------------|
|  Drilled Uniliner (hole near top) | trace, active samples, high recovery & linearity | 3.5mm 5.0mm x 54mm | — | 24974 | 24975 |
|  Drilled Uniliner (hole near bottom) | trace, active samples, high recovery & linearity | 3.5mm 5.0mm x 54mm | — | 22280 | 22281 |

*Nominal ID at syringe needle expulsion point.

tech tip

Drilled Uniliner® Liners

Use the Drilled Uniliner® liner with the hole near the bottom for semivolatile analysis or when compounds of interest could be affected by a tailing solvent peak. Use the Drilled Uniliner® liner with the hole near the top for chlorinated pesticides analysis, aqueous injections, as well as for analysis in which the compounds of interest elute away from the solvent peak.

Siltek® Treated Metal Inlet Liners for Varian GCs

- Won't crack, chip, or break like glass liners.
- Excellent response for pesticides, phenols, and other active compounds.

| Liner Type (3.8mm ID x 5.0mm OD x 54mm) | qty. | cat.# | price |
|---|-------|-------|-------|
| Split/Splitless | 5-pk. | 20711 | |
| Splitless Gooseneck | 5-pk. | 21002 | |





Introducing Sky™ Liners



See page 206 for more details.