

# High pressure fittings

POLYMERIC

Our high pressure fittings are rated up to 350 bar (5000 psi) with fingertight nuts, well beyond the burst strength of most PEEK tubing. These fittings are manufactured from high quality inert polymers to exacting tolerances.

## High pressure polymeric fittings index

### One-piece fittings

PEEK hex-head	
Over 5,000 psi	<b>NEW</b> ... page 19
5,000 psi	... 19
PEEK fingertight	
Color-coded	... 20
Natural	... 20
PPS hex-head	... 19
PEEK no-twist one piece fittings	... 21

### Nuts and ferrules

PEEK ferrules, over 5,000 psi	<b>NEW</b> ... 22
Single ferrule connections	... 22
Double ferrule connections	... 23
1/4-28 connections	... 25

### Plugs and caps

PEEK plugs	... 24
PEEK caps	... 24

### PEEK unions

Unions	... 26
Bulkhead unions	... 26
Reducing unions	... 27

### PEEK tees and crosses

Standard tees and crosses	... 28
Biocompatible mixing tee	... 28

### PEEK adapters

PEEK port and Luer adapters	... 29
-----------------------------	--------

### DISCLAIMER

The maximum holding pressure for any type of connections involving tubing and a ferrule varies considerably with the tubing material, the ferrule material, the clearance between tubing OD and ferrule ID, and the shape of the fitting detail.

### RELATED PRODUCTS

ChromBox kit	... 91
HPLC parts kit with PEEK and stainless fittings and tubing	
Fingertight adapters	
Color-It	... 17
Color-Sleeve	... 17
Nanovolume® high pressure fittings	... 36-39
PEEK starter kits	... 90
Tools for fittings	... 88-89

