

**Material Suffix Key**

- |                          |                                      |                         |                    |
|--------------------------|--------------------------------------|-------------------------|--------------------|
| -1 White Nylon           | -10 Acetal                           | -2 Black Nylon          | -3 Red Nylon       |
| -4 Green Nylon           | -5 Blue Nylon                        | -06 Orange Nylon        | -07 Yellow Nylon   |
| -6 Natural Polypropylene | -6005 Animal-Free Polypropylene      | -8003 Natural ABS       | -81 Lace White ABS |
| -9 Clear Polycarbonate   | -9002 Radiation Stable Polycarbonate | -J1A Natural Kynar PVDF |                    |

**MTLL450 (-1 -6 -9 -9002 -J1A)**  
Male Luer Integral Lock Ring to 400 Series Barb, 3/16" (4.8 mm) ID Tubing



**MTLL055 (-1 -2 -3 -4 -06 -07 -6 -6005 -9 -9002)**  
Male Luer Integral Lock Ring to 500 Series Barb, 1/4" (6.4 mm) ID Tubing



**MTLL360 (-1 -2 -6 -6005 -9 -9002 -J1A)**  
Male Luer Integral Lock Ring to 300 Series Barb, 1/4" (6.4 mm) ID Tubing



**MLRL004 (-1 -6 -9)**  
Male Luer to 500 Series Barb, 1/16" (1.6 mm) ID Tubing (May be used with separate rotating lock ring; FSLLR)



**MLRL007 (-1 -6 -9)**  
Male Luer to 500 Series Barb, 3/32" (2.4 mm) ID Tubing (May be used with separate rotating lock ring; FSLLR)



**MLRL013 (-1 -6 -9)**  
Male Luer to 500 Series Barb, 1/8" (3.2 mm) ID Tubing (May be used with separate rotating lock ring; FSLLR)



**MLRL025 (-1 -6 -9)**  
Male Luer to 500 Series Barb, 5/32" (4.0 mm) ID Tubing (May be used with separate rotating lock ring; FSLLR)



**MLRL035 (-1 -6 -9 -9002)**  
Male Luer to 500 Series Barb, 3/16" (4.8 mm) ID Tubing (May be used with separate rotating lock ring; FSLLR)



**MLRL055 (-1 -6 -9)**  
Male Luer to 500 Series Barb, 1/4" (6.4 mm) ID Tubing (May be used with separate rotating lock ring; FSLLR)



**FSLLR (-1 -2 -3 -4 -5 -06 -07 -6 -9 -9002)**  
Finger Snap Luer Lock Ring



**IT'S A LOCK WITH VALUE PLASTICS!**

Our MLRL and MSL Series of fittings can be used both as a slip luer or as a locking luer with the addition of our FSLLR luer lock ring, which allows color coding without flow path contact. Our MSL/FSLLR combination results in a stationary lock ring. Use a combination of MLRL and FSLLR to create a color coded rotating lock ring.

The MLRL allows FSLLR/lock ring rotation



The MSL has flanges which lock into the FSLLR, preventing rotation



Used together, you can create a color coded male luer with lock ring

