

Internal sample injectors, 1/16" fittings, 0.75 mm ports (.030")

UW Type

SPECS
1000 psi liq
175°C max
 Nitronic 60 valve body
 Valcon E rotor

Includes 2" standoff.
 Manual version has no
 standoff.

Standard electric actuator:
 110 VAC for USA
 110/230 VAC to 24 VDC power supply for international
 Microelectric actuator:
 24 VDC, with 110/230 VAC to 24 VDC power supply



Med temp
Internal sample
1/16" **0.75 mm**

OPTIONS

- 3", 4", and 6" standoffs
- Materials: Hastelloy C, Inconel 600, Monel 400, Nickel 200, Nitronic 50, Titanium, Zirconium (see pages 254-255)

Sample volume	.2 µl		.5 µl		1 µl		2 µl	
	Prod No	Price	Prod No	Price	Prod No	Price	Prod No	Price
Manual	CI4UWE.2		CI4UWE.5		CI4UWE1		CI4UWE2	
Manual with standoff	2CI4UWE.2		2CI4UWE.5		2CI4UWE1		2CI4UWE2	
With air actuator	A2CI4UWE.2		A2CI4UWE.5		A2CI4UWE1		A2CI4UWE2	
With std electric actuator	E2CI4UWE.2		E2CI4UWE.5		E2CI4UWE1		E2CI4UWE2	
With microelectric actuator	ED2CI4UWE.2		ED2CI4UWE.5		ED2CI4UWE1		ED2CI4UWE2	
Replacement valve	DCI4UWE.2		DCI4UWE.5		DCI4UWE1		DCI4UWE2	
Replacement rotor	SSACI4UWE.2		SSACI4UWE.5		SSACI4UWE1		SSACI4UWE2	

Internal sample injectors, 1/8" fittings, 0.75 mm ports (.030")

UW Type

SPECS
1000 psi liq
175°C max
 Nitronic 60 valve body
 Valcon E rotor

Includes 2" standoff.
 Manual version has no
 standoff.

Standard electric actuator:
 110 VAC for USA
 110/230 VAC to 24 VDC power supply for international
 Microelectric actuator:
 24 VDC, with 110/230 VAC to 24 VDC power supply




Med temp
Internal sample
1/8" **0.75 mm**

OPTIONS

- 3", 4", and 6" standoffs
- Materials: Hastelloy C, Inconel 600, Monel 400, Nickel 200, Nitronic 50, Titanium, Zirconium (see pages 254-255)

Sample volume	.2 µl		.5 µl		1 µl		2 µl	
	Prod No	Price	Prod No	Price	Prod No	Price	Prod No	Price
Manual	I4UWE.2		I4UWE.5		I4UWE1		I4UWE2	
Manual with standoff	2I4UWE.2		2I4UWE.5		2I4UWE1		2I4UWE2	
With air actuator	A2I4UWE.2		A2I4UWE.5		A2I4UWE1		A2I4UWE2	
With std electric actuator	E2I4UWE.2		E2I4UWE.5		E2I4UWE1		E2I4UWE2	
With microelectric actuator	ED2I4UWE.2		ED2I4UWE.5		ED2I4UWE1		ED2I4UWE2	
Replacement valve	DI4UWE.2		DI4UWE.5		DI4UWE1		DI4UWE2	
Replacement rotor	SSAI4UWE.2		SSAI4UWE.5		SSAI4UWE1		SSAI4UWE2	



UW Type
 1/8" fittings