

1/8" fittings, 1.0 mm ports (.040")

MWType

SPECS
 200 psi gas
 200°C max
 Nitronic 60 body
 Valcon E rotor

Includes 2" standoff.
 Ask about closemount assembly if valve will not be heated.

Standard electric actuators:
 110 VAC for USA
 110/230 VAC to 24 VDC power supply for international
 Microelectric actuators:
 24 VDC (includes a 110/230 VAC to 24 VDC power supply)

Low pressure
 SC
 Common outlet
 1/8" 1.0 mm

OPTIONS

- 4 and 8 positions available
- 3", 4", and 6" standoffs
- Materials: Hastelloy C, Inconel 600, Monel 400, Nickel 200, Nitronic 50, Titanium (see pages 254-255)
- Larger bore available except 16 position

	6 Position		10 Position		12 Position		16 Position	
	Prod No	Price	Prod No	Price	Prod No	Price	Prod No	Price
Manual (not recommended)	2SC6MWE		2SC10MWE		2SC12MWE		2SC16MWE	
With air actuator	A2SC6MWE		A2SC10MWE		A2SC12MWE		A2SC16MWE	
With standard electric actuator	E2SC6MWE		E2SC10MWE		E2SC12MWE		E2SC16MWE	
With microelectric actuator	EMT2SC6MWE		EMT2SC10MWE		EMT2SC12MWE		EMT2SC16MWE	
Replacement valve	DSC6MWE		DSC10MWE		DSC12MWE		DSC16MWE	
Replacement rotor	SSASC6MWE		SSASC10MWE		SSASC12MWE		SSASC16MWE	

1/4" fittings, 4.0 mm ports (.156")

MWType

SPECS
 100 psi gas
 75°C max
 Nitronic 60 body
 Valcon E2 rotor

Includes 2" standoff.
 Ask about closemount assembly if valve will not be heated.

Manual version not available.


Standard electric actuators:
 110 VAC for USA
 110/230 VAC to 24 VDC power supply for international
 Microelectric actuators:
 24 VDC (includes a 110/230 VAC to 24 VDC power supply)

Low pressure
 SC
 Common outlet
 1/4" 4.0 mm

OPTIONS

- 3", 4", and 6" standoffs
- Materials: Hastelloy C, Inconel 600, Monel 400, Nickel 200, Nitronic 50, Titanium (see pages 254-255)

	4 Position		6 Position		8 Position	
	Prod No	Price	Prod No	Price	Prod No	Price
With air actuator	AH2VLSC4MWE2		AH2VLSC6MWE2		AH2VLSC8MWE2	
With std electric actuator	E2VLSC4MWE2		E2VLSC6MWE2		E2VLSC8MWE2	
With microelectric actuator	EMT2VLSC4MWE2		EMT2VLSC6MWE2		EMT2VLSC8MWE2	
Replacement valve	DVLSC4MWE2		DVLSC6MWE2		DVLSC8MWE2	
Replacement rotor	SSAVLSC4MWE2		SSAVLSC6MWE2		SSAVLSC8MWE2	



SC
 6 positions
 1/4" fittings