

Systec® Debubbler Series

For Instrument Manufacturers

Remove bubbles, dissolved gas, or both!

Dissolved gases and bubbles in system liquids cause dispense volume anomalies in many instruments, negatively affecting both dispense precision and analytical accuracy. Now you have a choice of components for actively removing bubbles with or without also removing dissolved system gases. Online Vacuum Degassing offers operating convenience, high efficiency and low operating costs compared to other common degassing technologies.

Active Debubbler

In many low-pressure systems, such as diagnostic instruments, bubbles in the fluid stream can cause false detection readings and dispense anomalies. For these systems, the Systec® Active Debubbler captures and removes bubbles before they can affect the instrument or the results.

Degasser/Debubblers

For dispensing applications, removing both bubbles and dissolved gases from the flow path improves dispense precision and accuracy and enhances overall system performance. By combining vacuum degassing with active bubble removal, the Systec® Degasser/Debubblers both eliminate existing bubbles and actually prevent the formation of new bubbles by removing the dissolved gases before they can nucleate and cause problems.

Transfer-Line Degasser

In instruments where keeping the lowest internal volume is critical, a debubbler may not be the optimal choice. In these cases, it is possible to prevent bubble formation by degassing the system fluid in the transfer tubing itself. The Systec® Transfer-Line Degasser employs a unique co-axial approach to remove dissolved gases before they can form bubbles and affect critical results.




Precision Engineered Fluidics™

Debubbler Technical Data

- ▶ Standard Bubble Trap Sizes:
5 mL, 2.5 mL, and 0 mL (no bubble trap)
- ▶ Transfer Line Length:
2.5 mL size: 488.95 mm (19.25 in)
5.0 mL size: 977.9 mm (38.5 in)
- ▶ Debubbling / Degassing Membrane:
Proprietary Debubbling Membrane (chemical resistance similar to PTFE) or Teflon[®] AF
- ▶ Wetted Materials:
ETFE, Ultem[®], Debubbling Membrane or Teflon[®] AF
- ▶ Internal Volume:
1.1 mL in transfer line + bubble trap volume
- ▶ Liquid Connection:
3.18 mm (0.125 in) OD ETFE Tubing
- ▶ Vacuum Connection:
Barb-type fitting for 1.57 mm (.062 in) ID tubing
- ▶ Pressure Drop:
0.8 mm Hg / mL / min (assumes laminar flow and viscosity of 1 cP)
- ▶ Max Bubble Capacity:
2.5 mL or 5 mL depending on size of bubble trap



Effect of Degassing on Dispense Accuracy



Systec[™] is a registered trademark of Systec, LLC. Precision Engineered Fluidics is a trademark of IDEX Health & Science. © 2007. IDEX Corporation.

U.S. Patents Pending.
Created 7/07



ISO 9000:2001
FM 69754



www.chromtech.net.au E-mail : info@chromtech.net.au Tel : +61 3 9762 2034 Fax : +61 3 9761 1169