

Res-Sil™ C Packings

- Unique separation of saturated and unsaturated hydrocarbons.
- Innovative bonding chemistry for batch-to-batch reproducibility, excellent thermal stability, and long life.
- Wide range of bonded phases available.
- Equivalent to Waters Durapak® packings.

Bonded silica packings with *n*-octane or cyanopropyl (OPN) functional groups yield faster separations of C1 to C4 hydrocarbons, higher thermal stability, shorter conditioning times, and longer lifetimes than conventional packings. However, bonded silica packings have had inconsistent reproducibility and limited availability. Restek's research team has solved these age-old problems by developing Res-Sil™ C packings for consistent performance.

Unique Selectivity for Process GC and High-Speed Analysis of Petrochemicals

Res-Sil™ C bonded packings are ideal for fast resolution of difficult-to-separate saturated and unsaturated C4 hydrocarbons (e.g., see pages 114 and 115). This unique selectivity, when combined with other columns in series, provides petroleum and petrochemical method developers with a powerful tool for fast determination of C1 to C5 hydrocarbons.¹

Innovative Research and Stringent QA Provide Batch-to-Batch Consistency

Restek's synthesis procedure eliminates batch-to-batch variations. The amount of bonded liquid phase is precisely controlled in every batch, for reproducible retention times and separations. Each production batch of Res-Sil™ C packing is tested with a complex hydrocarbon mixture to meet demanding retention time and retention index specifications. Column bleed is also evaluated to ensure that there are no retention shifts or high baselines.

OPN on Res-Sil™ C Packing—the Latest in a Line of Bonded GC Phases

Restek offers a wide range of bonded packings for packed column GC, including Rtx®-1 and Stabilwax® phases, Carbowax® and *n*-octane phases on Res-Sil™ C packing, and our OPN on Res-Sil™ C packing. Each of these packings has low bleed, conditioning times of less than 30 minutes, long lifetime, and consistent batch-to-batch reproducibility. Every batch of Restek's bonded phases is tested for bleed, efficiency, and retention index and retention time reproducibility.

Res-Sil™ Packing Materials

Description	Temp. Limit (°C)	Mesh	Min. Qty.	cat.#
Res-Sil™ C	300	60/80	10g	25400
	300	80/100	10g	25028
Res-Sil™ B	300	60/80	10g	25401
	300	80/100	10g	25080
1% TCEP on Res-Sil™ B	175	80/100	10g	25081
OPN on Res-Sil™ C	150	80/100	10g	25042
<i>n</i> -Octane on Res-Sil™ C	150	80/100	10g	25030
2% Carbowax® 1540 on Res-Sil™ C	150	80/100	10g	25044

¹N.C. Saha, S.K. Jain, and R.K. Dua. *J. Chromat. Sci* 1978, 323-328.



Scott Harrison
Director of Marketing
1+ years of service!

also available

Custom packing materials are also available. See [page 126](#).

did you know?

Res-Sil™ replaces

- Poracil B
- Poracil C