

Volatile Organics Analysis

Rtx®-502.2 (proprietary Crossbond® diphenyl/dimethyl polysiloxane phase)

- Application-specific columns with unique selectivity for volatile organic pollutants. The Rtx®-502.2 column is cited in US EPA Method 502.2 and in many gasoline range organics (GRO) methods for monitoring underground storage tanks.
- Excellent separation of trihalomethanes; ideal polarity for light hydrocarbons and aromatics.
- Stable to 270°C.

similar phase

DB-502.2

An Rtx®-502.2 column will enable you to quantify all compounds listed in US EPA methods 502.2 or 524.2, whether you use a mass spectrometer or a PID in tandem with an ELCD. The diphenyl/dimethyl polysiloxane based Rtx®-502.2 stationary phase provides low bleed and thermal stability to 270°C. A 105-meter column can separate the light gases specified in EPA methods without subambient cooling. Narrow bore columns can interface directly in GC/MS systems.

Rtx®-502.2 Columns (fused silica)

(proprietary Crossbond® diphenyl/dimethyl polysiloxane phase)

ID	df (µm)	temp. limits	30-Meter	60-Meter	75-Meter	105-Meter
0.25mm	1.40	-20 to 250/270°C	10915	10916		
0.32mm	1.80	-20 to 250/270°C	10919	10920		10921
0.45mm	2.55	-20 to 250/270°C			10986	
0.53mm	3.00	-20 to 250/270°C	10908	10909		10910

ID	df (µm)	temp. limits	20-Meter	40-Meter
0.18mm	1.00	-20 to 250/270°C	40914	40915

also available

MXT® Columns

Rugged, flexible, Siltek® treated stainless steel tubing; inertness comparable to fused silica tubing. See pages 106 and 107 for our MXT®-502.2 and MXT® Volatiles columns.

similar phase

VOCOL®

Rtx®-Volatiles (proprietary Crossbond® diphenyl/dimethyl polysiloxane phase)

- Application-specific columns for volatile organic pollutants.
- Stable to 280°C.

Rtx®-Volatiles columns were the first columns designed specifically for analyses of the 34 volatile organic pollutants listed in US EPA methods 601, 602, and 624. With these columns, you can quantify all compounds listed in these methods, whether you use a mass spectrometer or a PID in tandem with an ELCD. The diphenyl/dimethyl polysiloxane based Rtx®-Volatiles stationary phase provides low bleed and thermal stability to 280°C. Narrow bore columns can interface directly in GC/MS systems.

Rtx®-Volatiles Columns (fused silica)

(proprietary Crossbond® diphenyl/dimethyl polysiloxane phase)

ID	df (µm)	temp. limits*	30-Meter	60-Meter	105-Meter
0.25mm	1.00	-20 to 270/280°C	10900	10903	
0.32mm	1.50	-20 to 270/280°C	10901	10904	
0.53mm	2.00	-20 to 270/280°C	10902	10905	10906

ordering note

Rtx®-Volatiles columns are available with Integra-Guard™ built-in guard columns. Get the protection without the connection! See page 30 for descriptions and ordering information.

it's a fact

Quantify all compounds in US EPA method 601, 602, or 624, using an Rtx®-Volatiles column.