

CarboBlack Solid Supports

Graphitized carbon black offers unique selectivity and very little adsorption for alcohol analyses. Two types of CarboBlack supports are available, CarboBlack B and CarboBlack C. CarboBlack B support, with its higher surface area, can hold up to a 10% loading of a nonsilicone liquid phase. CarboBlack C support can hold up to a 1% loading of a nonsilicone liquid phase. Many Carbowax® 20M-loaded CarboBlack packings are available. CarboBlack packings are treated with KOH or picric acid for basic or acidic compounds, and special alcoholic beverage loadings are available. CarboBlack supports provide resolution and retention similar to Carbopack™ and CarboGraph supports.

also **available**

CarboBlack packing materials. See **page 134**.



On CarboBlack B	Mesh	Stainless Steel Tubing					SilcoSmooth Tubing**				
		L (ft.)	OD (in.)	ID (mm)	cat.#**	price	L (m)	OD (in.)	ID (mm)	cat.#**	price
5% Carbowax 20M	80/120	—	—	—	—	—	2	1/8	2	80105-	
5% Carbowax 20M	60/80	6	1/8	2.1	88012-		1.8	1/8	2	80106-	
6.6% Carbowax 20M	80/120	6	1/8	2.1	80451-		2	1/8	2	80107-	
4% Carbowax 20M/ 0.8% KOH	60/80	—	—	—	—	—	2	1/8	2	80116-	
1% Rt-1000	60/80	8	1/8	2.1	88013-		2.4	1/8	2	80206-	
1% Rt-1000	60/80	6	1/8	2.1	80452-		2	1/8	2	80207-	
3% Rt-1500	80/120	10	1/8	2.1	80453-		3.05	1/8	2	80211-	
1% Rt-1510	60/80	10	1/8	2.1	80454-		3.05	1/8	2	80216-	
1.5% XE-60/1% H ₃ PO ₄	60/80	6	1/8	2.1	80455-		1.8	1/8	2	80305-	

On CarboBlack B	Mesh	Nickel 200 Tubing				
		L (m)	OD (in.)	ID (mm)	cat.#**	price
5% Krytox (Ni 200 tubing)	60/80	3.05	1/8	2.1	80127-	\$315

On CarboBlack C	Mesh	Stainless Steel Tubing					SilcoSmooth Tubing**				
		L (ft.)	OD (in.)	ID (mm)	cat.#**	price	L (m)	OD (in.)	ID (mm)	cat.#**	price
0.2% Carbowax 1500	60/80	6	1/8	2.1	80456-		2	1/8	2	80121-	
0.2% Carbowax 1500	80/100	6	1/8	2.1	80457-		2	1/8	2	80122-	
0.1% Rt-1000	80/100	6	1/8	2.1	80458-		1.8	1/8	2	80205-	
0.19% picric acid	80/100	6	1/8	2.1	80459-		2	1/8	2	80311-	
0.3% Carbowax 20M/0.1% H ₃ PO ₄	60/80	2.5	3/16	3.1	80460-		0.75	3/16	3.1	80111-	

Column Instrument Configurations



General Configuration
Suffix -800



Agilent 5880, 5890, 5987,
6890, 7890:
Suffix -810*



Varian 3700, Vista Series, FID:
Suffix -820



PE 900-3920, Sigma 1,2,3:
Suffix -830



PE Auto System 8300, 8400, 8700
Suffix -840

See page 143 for additional configurations.

Note: Initial 2" of column will be empty, to accommodate a needle. For a completely filled column (not on-column) add suffix -901.

*-810 suffix also includes 1-1/2" void on detector side.

Molecular Sieve Packed Columns

Molecular sieve packed columns easily separate permanent gases at above-ambient temperatures. Restek's R&D chemists have developed a process for preparing molecular sieve packings, which result in excellent batch-to-batch reproducibility. In addition, our molecular sieves are preactivated and ready to use. Each column comes with metal end-fittings to prevent water or carbon dioxide from adsorbing into the packing during shipment.

Molecular Sieve	Mesh	Stainless Steel Tubing					SilcoSmooth Tubing**				
		L (ft.)	OD (in.)	ID (mm)	cat.#**	price	L (m)	OD (in.)	ID (mm)	cat.#**	price
Molesieve 5A	60/80	6	1/8	2.1	80473-		2	1/8	2	80428-	
Molesieve 5A	80/100	3	1/8	2.1	88015-		1	1/8	2	80440-	
Molesieve 5A	80/100	6	1/8	2.1	80474-		2	1/8	2	80429-	
Molesieve 5A	80/100	10	1/8	2.1	88014-		3.05	1/8	2	80430-	
Molesieve 13X	60/80	6	1/8	2.1	80475-		2	1/8	2	80480-	
Molesieve 13X	80/100	6	1/8	2.1	80476-		2	1/8	2	80439-	

*Please add column instrument configuration suffix number to cat.# when ordering. See chart on this page.

**Siltek-treated stainless steel.

Custom

Packed/Micropacked
Column Request Form

See page 142 or visit
www.restek.com/packed

