

**Restek Thermolite® Septa**

- Usable to 340 °C inlet temperature.
- Precision molding assures consistent, accurate fit.
- Excellent puncturability.
- Preconditioned and ready to use.
- Do not adhere to hot metal surfaces.
- Packaged in precleaned glass jars.



Septum Diameter	25-pk./price	50-pk./price	100-pk./price
5mm (1/16")	27120	27121	27122
6mm (1/4")	27123	27124	27125
7mm	27126	27127	27128
8mm	27129	27130	27131
9mm	27132	27133	27134
9.5mm (3/8")	27135	27136	27137
10mm	27138	27139	27140
11mm (7/16")	27141	27142	27143
11.5mm	27144	27145	27146
12.7mm (1/2")	27147	27148	27149
17mm	27150	27151	27152
Shimadzu Plug	27153	27154	27155

**Restek IceBlue® Septa**

- Usable to 250 °C inlet temperature.
- Precision molding assures consistent, accurate fit.
- General-purpose septa.
- Excellent puncturability.
- Preconditioned and ready to use.
- Do not adhere to hot metal surfaces.
- Packaged in precleaned glass jars.
- Ideal for SPME.



Septum Diameter	50-pk./price	100-pk./price
9mm	27156	27157
9.5mm (3/8")	27158	27159
10mm	27160	27161
11mm (7/16")	27162	27163
11.5mm	27164	27165
12.7mm (1/2")	27166	27167
17mm	27168	27169
Shimadzu Plug	27170	27171

**BTO® Septa**

- Usable to 400 °C inlet temperature.
- Precision molding assures consistent, accurate fit.
- Partial predrilled CenterGuide design.
- Preconditioned and ready to use.
- Do not adhere to hot metal surfaces.
- Packaged in precleaned glass jars.
- Each batch GC/FID tested.
- Bleed and temperature optimized; ideal for demanding GC and GC/MS applications.



Septum Diameter	50-pk./price	100-pk./price
5mm CenterGuide	27100	27101
6mm (1/4")	27102	27103
9mm CenterGuide	27104	27105
9.5mm (3/8")	27106	27107
10mm	27108	27109
11mm (7/16") CenterGuide	27110	27111
11.5mm CenterGuide	27112	27113
12.7mm (1/2") CenterGuide	27114	27115
17mm CenterGuide	27116	27117
Shimadzu Plug	27118	27119

**HANDY**  
septum size chart

Instrument	Septum Diameter (mm)
<b>Agilent (HP)</b>	
5880A, 5890, 6850,	
6890, 7890, PTV	11
5700, 5880	9.5/10
On-Column Injection	5
<b>Thermo Scientific</b>	
TRACE GC	17
GCQ w/TRACE, PTV	17
8000 series	17
<b>Finnigan (TMQ)</b>	
GC 9001	9.5
GCQ	9.5
QCQ	9.5
TRACE 2000	9.5
<b>PerkinElmer</b>	
Sigma series	11
900,990	11
8000 series	11
Auto SYS	11
Auto SYS XL	11
<b>Shimadzu</b>	
All models	Plug
<b>SRI</b>	
All models	Plug
<b>Tracor</b>	
540	11.5
550,560	9.5
220,222	12.5
<b>Varian</b>	
Injector type:	
Packed column	9.5/10
1078/1079	10/11
1177	9
1075/1077	11

for **more info**How **Hot** is Your Septum?[www.restek.com/cat002](http://www.restek.com/cat002)**i tech tip****Tips for Handling Septa**

All septa, regardless of composition, puncturability, or resistance to thermal degradation will fail if they are mishandled. Overtightening a septum nut invariably will reduce septum lifetime by increasing coring/splitting. All septa contain volatile materials (e.g., phthalates) that are released when the septum is heated (septum bleed). Because most GCs are equipped with a septum purge, septum bleed generally will disappear within 30 minutes after installing a new septum and exposing it to normal injector temperatures. All Restek septa are preconditioned and are ready to use without delay.

**Note:** Due to the injection port temperatures, Restek recommends using only BTO septa in Thermo Scientific instruments.