

Nuts

Internal nuts – stainless steel

Nuts with product numbers starting with Z are for use with all standard Valco internal fittings and most valves. They may be used with fittings from other manufacturers as well. The L (long) and XL (extra-long) types are for situations where the fitting head may be otherwise inaccessible or where interference between fittings exists, as on many Valco multiposition valves. Standard material is 300 series stainless.



Stainless nuts			
Package of 10:	Length	Prod No	Price
1/32" nut	.30"	ZN.5-10	
1/32" nut	.45"	LZN.5-10	
1/16" nut	.43"	ZN1-10	
1/16" nut	.50"	MZN1-10	
1/16" nut	.75"	LZN1-10	
1/16" nut	1.00"	XLZN1-10	
1/8" nut	.57"	ZN2-10	
1/8" nut	.82"	LZN2-10	
1/8" nut	1.07"	XLZN2-10	
1/4" nut	.70"	ZN4-10	
1/4" nut	1.11"	LZN4-10	



NEW Specialty nuts – stainless steel

These special purpose nuts facilitate a tight bend as the tube exits the fitting, and can also help prevent kinks in very thin wall tubing. Quick bend nuts are available in standard length (.43") and in a short version (.30") for certain custom applications. Note that the short version (ZSN1) can *only* be used in certain applications. Call for more information.

Stainless nuts			
Description	Length	Prod No	Price
1/16", standard	.43"	ZN1Q	
1/16", short	.30"	ZSN1	



MORE INFORMATION

PEEK nuts	page 63
HPLC column end fittings	43-46
Reducing unions	
Internal	29
External	30
External/internal	31
Internal/external	31
Unions	
Internal	26
External	27
External/internal	27

TECH TIP

Fittings for **360 micron** tubing are available on pages 57-58.

0.25 mm =	.010"
0.50 mm =	.020"
0.75 mm =	.030"
1.0 mm =	.040"
1.5 mm =	.060"
2.0 mm =	.080"
4.6 mm =	.180"
6.0 mm =	.236"
6.4 mm =	.253"
7.0 mm =	.275"
10.0 mm =	.400"
27.0 mm =	1.08"
1/32" =	0.8 mm
1/16" =	1.6 mm
1/8" =	3.2 mm
1/4" =	6.4 mm
3/8" =	9.5 mm
1/2" =	12.7 mm

Ferrules

Valco metal ferrules cut a ring near the end of the tube, preventing tube release at high pressures without significantly deforming and restricting the tube interior. (However, if the hardness of the tubing is equal to or greater than that of the ferrule, deformation of the tube rather than a cut ring is likely.) Make up usually takes only about a 1/4 turn beyond the point where the ferrule first starts to grab the tubing. Polymeric ferrules seal by the increased friction from compression.

Valco zero volume ferrules may be used with all Valco fittings and with those of most other manufacturers. The maximum pressure limit is generally determined by the yield strength of the tubing. The maximum pressure for softer materials (such as brass and polymers) is lower, and depends on the tubing used. If in doubt about a particular combination, consult our technical staff.

For trace gas analysis, use gold-plated ferrules to achieve sealing with $<10^{-9}$ cc/atm/sec leakage.



MORE INFORMATION

For more detailed information on metals, refer to the discussion on pages 254-255.

Metal ferrules

	Prod No	Price	Prod No	Price	Prod No	Price
Package of 10:	Stainless, Type 303		Stainless, Type 316		Stainless, Gold-plated	
1/32"	ZF5-10		ZF5S6-10	\$40	ZF5GP-10	
1/16"	ZF1-10		ZF1S6-10	30	ZF1GP-10	
1/8"	ZF2-10		ZF2S6-10	22	ZF2GP-10	
1/4"	-		ZF4S6-10	19	ZF4GP-10	
Sold individually:	Hastelloy C		Nickel		Titanium	
1/32"	ZF5HC		ZF5NI	\$9	ZF5TI	
1/16"	ZF1HC		ZF1NI	8	ZF1TI	
1/8"	ZF2HC		ZF2NI	8	ZF2TI	
1/4"	ZF4HC		ZF4NI	9	ZF4TI	
Package of 10:	Brass					
1/32"	ZF5B-10					
1/16"	ZF1B-10					
1/8"	ZF2B-10					
1/4"	ZF4B-10					

- Not available

Larger sizes and/or specific materials may be available on special order.

METALS

AT A GLANCE

Hastelloy C®HC
Resistant to pitting;
Resists oxidizing atmospheres

Nickel NI
Resistant to caustics,
high temp halogens,
and hydrogen halides

Stainless steel,
Gold-platedGP
More inert than standard stainless

Stainless steel,
Type 303
GC, gas lines, general purpose

Stainless steel,
Type 316S6
LC with high chloride ion in solutions

TitaniumTI
Outstanding resistance to most media except hydrofluoric acids

Brass B
Not recommended for most chromatographic applications

0.25 mm = .010"
0.50 mm = .020"
0.75 mm = .030"

1.0 mm = .040"
1.5 mm = .060"
2.0 mm = .080"

4.6 mm = .180"
6.0 mm = .236"
6.4 mm = .253"

7.0 mm = .275"
10.0 mm = .400"

27.0 mm = 1.08"

1/32" = 0.8 mm
1/16" = 1.6 mm
1/8" = 3.2 mm

1/4" = 6.4 mm
3/8" = 9.5 mm
1/2" = 12.7 mm