

## HPLC Injectors

### Internal sample injectors, 1/16" fittings, 0.40 mm ports (.016") 0.25 mm column port diameter (.010")

W Type

**5,000 psi**  
**Internal sample**  
**1/16" 0.40 mm**

Standard electric actuator:  
110 VAC for USA  
110/230 VAC to 24 VDC power supply for international  
Microelectric actuator:  
24 VDC, with 110/230 VAC to 24 VDC power supply.



**SPECS**  
**5000 psi liq**  
**75°C max**  
Nitronic 60 valve body  
Valcon H rotor

Sample volume	.06 µl		.1 µl		.2 µl		.5 µl	
	Prod No	Price	Prod No	Price	Prod No	Price	Prod No	Price
Manual	CI4W.06		CI4W.1		CI4W.2		CI4W.5	
With air actuator	ACI4W.06		ACI4W.1		ACI4W.2		ACI4W.5	
With standard electric actuator	ECI4W.06		ECI4W.1		ECI4W.2		ECI4W.5	
With microelectric actuator	EPCI4W.06		EPCI4W.1		EPCI4W.2		EPCI4W.5	
Replacement valve	DCI4W.06		DCI4W.1		DCI4W.2		DCI4W.5	
Replacement rotor	SSACI4W.06		SSACI4W.1		SSACI4W.2		SSACI4W.5	



W Type  
1/16" fittings

**OPTIONS**

- 2", 3", 4", and 6" standoffs
- Materials: Hastelloy C, Inconel 600, Monel 400, Nickel 200, Nitronic 50, Titanium, Zirconium (see pages 254-255)
- 1/32" fittings with 0.25 mm bore (.010") also available. Consult factory for product number and pricing.



UW Type  
1/16" fittings

### Internal sample injectors, 1/16" fittings, 0.75 mm ports (.030")

UW Type

**5,000 psi**  
**Internal sample**  
**1/16" 0.75 mm**

Standard electric actuator:  
110 VAC for USA  
110/230 VAC to 24 VDC power supply for international  
Microelectric actuator:  
24 VDC, with 110/230 VAC to 24 VDC power supply.



**SPECS**  
**5000 psi liq**  
**75°C max**  
Nitronic 60 valve body  
Valcon H rotor

Sample volume	.2 µl		.5 µl		1 µl		2 µl	
	Prod No	Price	Prod No	Price	Prod No	Price	Prod No	Price
Manual	CI4UW.2		CI4UW.5		CI4UW1		CI4UW2	
With air actuator	ACI4UW.2		ACI4UW.5		ACI4UW1		ACI4UW2	
With standard electric actuator	ECI4UW.2		ECI4UW.5		ECI4UW1		ECI4UW2	
With microelectric actuator	EDCI4UW.2		EDCI4UW.5		EDCI4UW1		EDCI4UW2	
Replacement valve	DCI4UW.2		DCI4UW.5		DCI4UW1		DCI4UW2	
Replacement rotor	SSACI4UW.2		SSACI4UW.5		SSACI4UW1		SSACI4UW2	

**OPTIONS**

- 2", 3", 4", and 6" standoffs
- Materials: Hastelloy C, Inconel 600, Monel 400, Nickel 200, Nitronic 50, Titanium, Zirconium (see pages 254-255)
- 1/32" fittings with 0.25 mm bore (.010") also available. Consult factory for product number and pricing.

CHROMalytic TEChnology Pty Ltd AUSTRALIAN Distributors e-mail: sales@chromtech.net.au Tel: 03 9762 2034