




With Valco Zero Dead Volume (ZDV) Fittings

C20Z valves with zero dead volume fittings (10-32 thread) are shipped with standard PEEK nuts and ferrules. Zero dead volume fingertight fittings and nuts and ferrules of other materials may be ordered separately. Standard specifications are 100 psi gas/250 psi liquid at 75°C. On request, the pressure rating can be as high as 600 psi liquid.

Caution: Metal fittings will damage the threads and details of C20Z series valves. Use of metal fittings in a C20Z valve voids the warranty.


The **Model C22Z** is a conventional two position sample injector and switching valve, with 4, 6, 8, or 10 ports. Sample injection requires a loop, ordered separately.

The **Model C24Z** is an internal sample injector, for applications in which the sample size is smaller than that of any available external loop. Sample sizes available are 0.2, 0.5, and 1 µl.



Model C22Z
page 164

10-32 ZDV



Model C24Z
page 166

10-32 ZDV

Internal sample


With Cheminert 1/4-28 Fittings

C20 Series valve caps have female threads for direct connection of lines – no couplings are required. C20 Series valves are available in 4, 6, 8, and 10 port versions. Standard specifications are 100 psi gas/250 psi liquid at 75°C.

Multicolored Cheminert 1/4-28 flangeless fittings for 1/16" or 1/8" OD tubing (depending on the valve model) are included.

Model C22 valves are used for sample injection or switching. (Functionally equivalent to Model C22Z) Sample injection requires a loop, ordered separately.

The **Model C24** is an internal sample injector like the C24Z, available with 0.5, 1.0, or 2.0 µl sample size.



Model C22
page 165

1/4-28 Int.



Model C24
page 167

1/4-28 Int.

Internal sample

MORE INFORMATION

Decoding
Cheminert valve
product no's... 264-265

Actuation 186-209

Applications .. 168-169

Materials

Metals..... 254-255
Polymers 256
Valve rotors..... 257

Valve descriptions

Cheminert
injectors..... 146-149
selectors..... 150-151
nanovolume®..... 146
Diaphragm 140-141
Valco
injectors..... 99
selectors..... 100-101

Cheminert valve prices

HPLC..... 152-163
Low pressure .. 164-167
Nanovolume®
..... 152-155, 170-171
Selectors 170-177
OEM..... 178-185

CAUTION

Metal fittings will damage the threads and details of C20Z series valves (models C22Z, C24Z, C25Z). Use of metal fittings in a C20Z valve voids the warranty.

TECH TIP

Our life tests indicate that these valves will typically give more than 100,000 cycles before requiring any service. This assumes that the fluid used is free of particulates and not reactive toward the valve components. If the stream may contain particulates, or if it has high salt content which could precipitate within the sample lines, use an in-line filter.

Note: Valves with purge ports are available on request.