

CHECK VALVES



**ONE WAY CHECK VALVES
PG-12**



**ANTI-SIPHON CHECK VALVES
PG-13**



**DOUBLE CHECK VALVES,
TUBING POCKET CHIMNEY PORT
PG-15**



**DOUBLE CHECK VALVES,
FEMALE LUER CHIMNEY PORT
PG-15**



THE SCV SERIES

CHECK VALVES

SCV Series products are available in anti-siphon or one-way check valve configurations in a variety of materials and end fitments. The valves feature low priming volume, ease of removing air bubbles during priming and operate in any spatial orientation. All products feature DEHP- and latex-free silicone diaphragms and all materials of construction satisfy USP Class VI and ISO 10993 criteria.

SCV01092 (Blue and Clear Polycarbonate w/Silicone Diaphragm)
Check Valve, Socket for .122" (3.1 mm) ID x .165" (4.2 mm) OD Tubing x 2



Cracking Pressure: $\leq .174$ psig
Max. Back Pressure: 87.023 psig
Flow Rate: ≥ 90 ml/min
Flow Direction: Left to right

SCV08053 (White SAN w/Silicone Diaphragm w/Natural LDPE)
Check Valve, Female Locking Luer to Male Locking Luer w/Cap



Cracking Pressure: $\leq .174$ psig
Max. Back Pressure: 87.023 psig
Flow Rate: ≥ 90 ml/min
Flow Direction: Left to right

SCV10090 (Clear Polycarbonate w/Silicone Diaphragm)
Check Valve, Female Locking Luer to Pocket for .118" (3.0 mm) OD Tubing



Cracking Pressure: $\leq .174$ psig
Max. Back Pressure: 87.023 psig
Flow Rate: ≥ 90 ml/min
Flow Direction: Left to right

SCV17090 (Clear Polycarbonate w/Silicone Diaphragm)
Check Valve, Female Locking Luer to Socket for .118" (3.0 mm) ID x .161" (4.1 mm) OD Tubing



Cracking Pressure: $\leq .174$ psig
Max. Back Pressure: 87.023 psig
Flow Rate: ≥ 90 ml/min
Flow Direction: Left to right



VALUE PLASTICS, INC.

HRM *Medical* +61(0)3 9762 2034
ECH *Technology* Pty Ltd

Australian Distributors:
Importers & Manufacturers