

**VPSS401068N (Polycarbonate with Silicone Disk)**

Check Valve, Male/Female Luer, 420 mL/min flow rate at 1 M head 30 psi back pressure, 1/4 psi inlet cracking pressure



**VPSS401020N (Polycarbonate with Silicone Disk)**

Check Valve, Male/Female Luer, 129 mL/min flow rate at 100mmHg, 45 psi back pressure, 1-5 psi inlet cracking pressure



**VPSS401036SN (Polycarbonate with Silicone Disk)**

Reflux Check Valve, Male/Female Luer, 350mL/min flow Rate at 1 M head, 45 psi back pressure, opens at 284 mmHg



**VPSS401001N (ABS Housing with Silicone Disk)**

Check Valve, Male Slip Luer, 420 mL/min flow rate at 1 M head, 30 psi back pressure, 1/4 psi inlet cracking pressure



**VPM2930601N (White ABS)**

Tube Clamp with split, 1/8" (3.2 mm) OD Tubing



**VPS3901074N (Polyisoprene with ABS Acrylic Body)**

IN-4000 Intermittent Injection Site to Male Luer Lock



**VPM1060200N (Clear Low Density Polyethylene)**

Long Spike Guard Closed at Tip



**VPM0480201N (White Polyethylene)**

Luer Tip Syringe Cap



**VPB0850400N (Clear ABS)**

Female Luer Thread Style Coupler



**VPM1080303N (Blue Polyethylene)**

Male Luer Integral Lock Ring Plug



**VPB1000055N (Polycarbonate Body with Polyethylene Handle)**

One way Stopcock, Male Slip Luer to Capped Female Luer Thread Style



**VP455980 (Polycarbonate Body with Polyethylene Handle)**

One Way Stopcock, Capped Male Luer Lock to Capped Female Luer Thread Style - Sterile Version



**VPB1000079N (Polycarbonate Body with Polyethylene Handle)**

Three Way Stopcock, (2) Capped Female Luer Thread Style and Capped Male Luer Lock



**VPB1000062N (Polycarbonate Body with Polyethylene Handle)**

Three Way Stopcock, (2) Female Luer Thread Style and Male Slip Luer



VALUE PLASTICS, INC.

HRM acrylic +61(0)3 9762 2034  
ECHNology Pty Ltd

Australian Distributors:  
Importers & Manufacturers

OTHER COMPONENTS